



Taylor Cabinet Door Company

Hanging the Doors with our Hinges

Removing the hinge plate from the hinge.



1. Grasp the hinge by the hinge “cup” in one hand.



2. Using your other hand press the release lever on the back of the hinge plate.



3. Pull the hinge plate back.



4. The hinge plate will release from the hinge.



Tools needed. Phillips screw driver, a screw gun with a #2 Phillips tip.

1. Start by installing the upper hinge plates on the cabinet face frame by using another hinge plate as a spacer. Use $\frac{3}{4}$ " phillips screws, you may need to drill a pilot hole.



2. Install the hinges on the doors by placing them into the pre-drilled holes. With your screw driver turn the hinge screws 180° to lock the hinge to the door.

Note: Do not use a screw gun, you will only be turning $1/2$ turn. The head of the screw can easily strip with a screw gun.

Hanging The Doors with our Hinges



3. Clip the hinge plate on the lower door hinge by pushing the plate forward into the hinge slots and squeezing the hinge and plate together, the back release will snap forward.



4. Attach the door to the upper hinge plate that you attached to the cabinet face frame.



5. With the door open it will hang in place by itself allowing you to screw the lower plate to the cabinet face frame.

Tip: If you need to remove the door from the cabinet, simply hold the door and pressing the release at the back of the hinges.



6. If the door is not sitting flat on the cabinet, you will need to adjust the hinge plate screw. For the side to side alignment you will need to adjust the hinge screw.



7. Install the clear door bumpers at the top & bottom corners of the doors & drawers.